

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Appl. No. : 10/524,800
Applicant : Farrar et al.
Filed : January 17, 2006
Art Unit : 3775
Examiner : Nicholas W. Woodall

Confirmation No. 5890

MMB Docket No. : 1781-0017
Urquhart Reference : SJB/P11755US

For: Guide Block for Use in Surgery

I hereby certify that this correspondence is being transmitted via the Electronic Filing System (EFS) to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on:

May 20, 2009

Date of Deposit

Paul J. Maginot

Name of person mailing Document or Fee

/Paul J. Maginot/

Signature

May 20, 2009

Date of Signature

AMENDMENT

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

In response to the Office Action dated December 22, 2008 (hereinafter "the Office Action"), please amend the above-identified application as follows and enter the following remarks:

Amendments to the Claims are reflected in the listing of claims which begins on page 3 of this paper. Amendments to Title, Drawings, and Specification are reflected on page 2.

Remarks/Arguments begin on page 8 of this paper.

AMENDMENT TO TITLE

Please amend the title of the invention as follows:

Surgical Assembly having a Guide Block for Use in Surgery

AMENDMENT TO DRAWINGS

Please amend FIG. 1 to include a blade of a surgical tool shown extending through the slot 10 of the guide part 6 as depicted in the Annotated Sheet attached hereto.

AMENDMENT TO SPECIFICATION

Please delete paragraph [0026] of the specification identified in the published patent application (see Pat. App. Pub. No. 2006/0155291), and substitute the following paragraph in its place (underlining showing the changes made relative to its previous version):

[0026] The guide part 6 of the fixation block has a slot 10 in it. The slot extends through the guide part so that a blade 11 of a surgical tool 13 (schematically shown in phantom) inserted into the slot can extend through it and be used to cut a bone to which the guide block is fixed. The slot will be dimensioned so that the blade is a sliding fit, as in existing cutting blocks.